

Complies with OSHA's Hazard Communication Standard 29
CFR 1910.1200.

DATE OF PREPARATION: January 1998

DATE OF REVISION: September 11, 2009

GOODSON
Tools and Supplies for Engine Builders
156 Galewski Drive • P.O. Box 847 • Winona, MN 55987-0847
Toll-Free 1-800-533-8010 • Local 507-452-1830 • www.goodson.com

1. IDENTIFICATION

Part No & Description: ALB-1 Last Blast Aluminum Paint

Emergency Phone: 800-688-4005 (24 hours)

2. COMPOSITION/DATA ON COMPONENTS

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous Components:

108-88-3 Toluene	23.46%
67-64-1 Acetone	23.14%
74-98-6 propane	17.63%
106-97-8 n-butane	10.35%
1317-65-3 Calcium Carbonate	4.88%
7429-90-5 aluminum powder (stabilised)	3.69%
64742-47-8 Mineral Spirits	1.58%
1330-20-7 xylene (mix)	1.44%

3. HAZARDS IDENTIFICATION

Hazard Description: Harmful. Extremely Flammable.

Physical dangers: Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame. Has narcotizing effect. Extremely flammable. Irritating to eyes and skin. Keep out of the reach of children.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA Ratings (scale 0-4): Health=1 Fire=4 Reactivity=3

HMIS ratings (scale 0-4): Health=1 Fire=4 Physical Hazard=3

4. FIRST AID MEASURES

After Inhalation: Supply fresh air; consult doctor in case of complaints.

After Skin Contact: Immediately wash with water and soap and rinse thoroughly.

After Eye Contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After Swallowing: Contact physician or poison control center.

5. FIRE FIGHTING MEASURES

Extinguishing Agents: CO₂, sand, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam

Protective equipment: No special measures required.

6. ACCIDENTAL RELEASE MEASURES

Personal Safety: Wear protective equipment. Keep unprotected persons away.

Environmental Safety: Do not allow product to reach sewage systems or ground water.

Clean-up/Collection: Ensure adequate ventilation.

7. HANDLING AND STORAGE

Fire/Explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with limit values that require monitoring at the workplace:

108-88-3 Toluene

PEL: Short-term value: C 300; 500* ppm

Long-term value: 200 ppm

*10-min peak per 8-hr shift

REL: Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV: 75 mg/m³, 20 ppm

67-64-1 Acetone

PEL: 2400 mg/m³, 1000 ppm

REL: 590 mg/m³, 250 ppm
TLV: Short-term value: 1782 mg/m³, 750 ppm
Long-term value: 1188 mg/m³, 500 ppm
BEI

74-98-6 propane

PEL: 1800 mg/m³, 1000 ppm
REL: 1800 mg/m³, 1000 ppm
TLV: Varies mg/m³, 1000 ppm

106-97-8 n-butane

REL: 1900 mg/m³, 800 ppm
TLV: Varies mg/m³, 1000 ppm

7429-90-5 aluminum powder (stabilised)

PEL: 15*, 5**mg/m³
Metal dust *total dust **respirable fraction
REL: 10*, 5** mg/m³
Metal dust *total dust **respirable fraction
TLV: 1* mg/m³
*as respirable fraction

1330-20-7 xylene (mix)

PEL: 435 mg/m³, 100 ppm
REL: Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm
TLV: Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection: Tightly sealed goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information:

Odor: Aromatic

Flash point: -19°C

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120°F. In use, may form flammable/explosive vapor-air mixture.

Lower Explosion Limit: 1.5 Vol %

Vapor pressure: 40 PSI, 2750 hPa

Specific Gravity: Between 0.77 and 0.85 (water equals 1.00)

VOC content (less exempt solvents): 56.1%

Solids Content: 20.7%

Boiling point: -44°C

Auto igniting: Product is not selfigniting.

Upper Explosion Limit: 10.9 Vol %

Density @ 20°C: 0.77636 g/cm³

VOC content: 563.6 g/l / 4.70 lb/gal

MIR Value: 1.44

10. STABILITY & REACTIVITY

Conditions to avoid: Do not allow the can to exceed 120°F. Stable at normal temperatures.

Hazardous Reactions: No dangerous reactions known.

11. TOXICOLOGICAL INFORMATION

Skin effects: Irritant to skin and mucous membranes.

Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12. ECOLOGICAL INFORMATION

Other Information: This product does not contain any chlorofluorocarbons (CFC's), or chlorinated solvents.

Aquatic toxicity: Hazardous for water, do not empty into drains.

13. DISPOSAL CONSIDERATIONS

Disposal Method: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate or compact.

Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14. TRANSPORTATION

Hazard Class: 2.1

Label: 2.1

Identification Number: N/A

ADR/RID/TDG class: 2 5F Gases

UN-Number: 1950
Packaging Group: II
Marine pollutant: No
Proper Shipping Name: Aerosols, Flammable Consumer Commodity ORM-D

IMDG Class: 2.1
EMS Number: F-D, S-U
ICAO/IATA Class: 2.1

15. REGULATIONS

SARA Section 355 (extremely hazardous substances): None of the ingredients in this product are listed.

SARA Section 313 (specific toxic chemical listings):

108-88-3 Toluene

7429-90-5 Aluminum powder (stabilised)

1330-20-7 xylene (mix)

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

California Proposition 65 Chemicals known to cause developmental toxicity: 108-88-3 Toluene

CANADIAN

ENVIRONMENTAL PROTECTION ACT: EPA: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA: A=Known human carcinogen B=Probable human carcinogen
C=Possible human carcinogen
D=Not classifiable as to human carcinogenicity: Inadequate human & animal evidence of carcinogenicity (or no data is available).
I: 'Data are inadequate for an assessment of human carcinogenic potential.'
II: 'Inadequate information to assess carcinogenic potential.'

108-88-3 Toluene II

67-64-1 Acetone I

1330-20-7 xylene (mix) I

IARC: Group 2A: The ingredient is probably carcinogenic to humans.

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3 Toluene 3

1330-20-7 xylene (mix) 3

ACGIH: A1-designates a confirmed human carcinogen.
A2-designates a suspected human carcinogen.
A3-designates an animal carcinogen.
A4-designates "not classifiable as a human carcinogen".

108-88-3 Toluene A4

67-64-1 Acetone A4

7429-90-5 Aluminum powder (stabilised) A4

1330-20-7 xylene (mix) A4

NIOSH: The following substances are regulated in the United States with reference to occupational exposure limits:

Risk Phrases: Extremely flammable. Irritating to eyes and skin.

Safety phrases: Keep out of the reach of children. Do not breath gas/fumes/vapor/spray. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing and gloves. In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.

If swallowed, seek medical advice immediately and show the container or label. Use only in well-ventilated areas.

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

IMDG: International maritime Code for Dangerous Goods.
DOT: US Department of Transportation.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
PP: Severe Marine Pollutant
P: Marine Pollutant
CAS: Chemical Abstracts Service (division of the American Chemical Society).
NFPA: National Fire Protection Association (USA).
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
ISO: International Organization for Standardization.
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer.
NIOSH: National Institute for Occupational Safety and Health.
TSCA: Toxic Substances Control Act.
CPSC: Consumer Product Safety Commission

