

Material Safety Data Sheet

CLB-58

Complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200.

GOODSON

Tools and Supplies for Engine Builders
Airport Industrial Park • P.O. Box 847 • Winona, MN 55987-0847
Toll-Free 1-800-533-8010 • Local 507-452-1830 • www.goodson.com

DATE OF PREPARATION: January 23, 1998

1. IDENTIFICATION

Part No. and Description: CLB-58 Color Last Blast-GM Black 12 oz.

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt/Wt% less than</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-Ceiling</u>	<u>TLV-TWA</u>	<u>Skin</u>
Acetone	00067-64-1	30.0%	750 ppm	1000 ppm	750 ppm	1000 ppm	n/e	Yes
Toluol	00108-88-3	20.0%	50 ppm	n/e	100 ppm	150 ppm	n/e	Yes
Propane	00074-98-6	20.0%	1000 ppm	n/e	1000 ppm	n/e	n/e	No
N-Butane	00106-97-8	10.0%	800 ppm	n/e	800 ppm	n/e	n/e	No
Glycol Ether EP	02807-30-9	10.0%	25 ppm	n/e	25 ppm	n/e	n/e	Yes
Methyl Iso-butyl Ketone	00108-10-1	5.0%	50 ppm	75 ppm	50 ppm	75 ppm	n/e	Yes
Propylene Glycol								
Monomethyl Ether Acetat	00108-65-6	5.0%	n/e	n/e	n/e	n/e	n/e	No
Mineral Spirits	64742-47-8	5.0%	100 ppm	n/e	500 ppm	n/e	n/e	Yes

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: May cause flash fire or explosion.

Effects of Overexposure-Eye Contact: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, red- dening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

Effects of Overexposure-Skin Contact: Causes skin irritation. Allergic reactions are possible. Prolonged or repeated contact can re- sult in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Effects of Overexposure-Inhalation: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor and skin exposure. Prolonged inhalation may be harmful.

Effects of Overexposure-Ingestion: This material may be harmful or fatal if swallowed. Irritating to mouth, throat and stomach.

Effects of Overexposure-Chronic Hazards: Possible reproductive hazard.

Primary Route(s) of Entry: Skin Absorption, Inhalation, Ingestion, Eye Contact, Skin Contact

4. FIRST AID MEASURES

First Aid-Eye Contact: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

First Aid-Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

First Aid-Inhalation: Remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult give oxygen, Keep victim warm. Get immediate medical attention.

First Aid-Ingestion: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flash Point: -4°F **Lower Explosive Limit:** 0.7% **Upper Explosive Limit:** 12.8%

Extinguishing Media: Water Fog, Dry Chemical, CO2, Alcohol Foam, Foam

Unusual Fire & Explosion Hazards: Vapors may form explosive mixture with air.

Special Firefighting Procedures: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL SPILL PROCEDURES

Steps to be taken in case material is released or spilled: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. HANDLING AND STORAGE

Handling: Wash thoroughly after handling **Storage:** Keep away from heat, sparks and flame.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be per- missible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, ex- posure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Skin Protection: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

Eye Protection: Wear safety glasses with side shields (or goggles) and a face shield.

EXPOSURE CONTROLS / PERSONAL PROTECTION CONT...

Other Protective Equipment: Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

Hygienic Practices: No information

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Range:	-44 - 389°F	Vapor Density:	Is heavier than air	Odor:	Aromatic
Odor Threshold:	n/a	Appearance:	Liquid	Evaporation Rate:	Is faster than Ether
Solubility in H2O:	Slight	Freeze Point:	n/a	Specific Gravity:	0.7594
Vapor Pressure:	40 psi	pH @ 0.0%:	n/a	Physical State:	Liquid
Viscosity:	n/a				

10. STABILITY AND REACTIVITY

Conditions to Avoid: Do not store above 120°F, Keep away from sparks, pilot lights, and/or open flames.

Incompatibility: No Information

Hazardous Decomposition Products: May produce hazardous fumes when heated to decomposition. Fumes may contain carbon dioxide and/or carbon monoxide.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

Ecological Information: This product does not contain chlorinated solvents or lead.

13. DISPOSAL CONSIDERATIONS

Disposal Method: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact.

14. TRANSPORTATION INFORMATION

DOT Proper Shipping Name: Consumer Commodity ORM-D

DOT Technical Name: n/a

DOT Hazard Class: n/a

DOT UN/NA Number:

Packing Group:

Hazard Subclass:

Resp. Guide Page:

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS-AS FOLLOWS:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

CERCLA-SARA Hazard Category: This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 & 312 of the Superfund Amendment & Reauthorization Act of 1986 (SARA Title III) & is considered, under applicable definitions, to meet the following categories: Immediate Health Hazard, Chronic Health Hazard, Fire Hazard, Pressurized Gas Hazard

SARA Section 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt/Wt% less than</u>
Toluol	00108-88-3	20.0%
Glycol Ether EP	02807-30-9	10.0%
Methyl Iso-butyl Ketone	00108-10-1	5.0%
Xylene	01330-20-7	1.0%
Ethyl Benzene	00100-41-4	1.0%
Methanol	00067-56-1	0.1%

US STATE REGULATIONS-AS FOLLOWS:

New Jersey Right-to-Know: The following materials are non-hazardous, but are among the top five components in this product:

<u>Chemical Name</u>	<u>CAS No.</u>
Acrylic Resin	n/a

Pennsylvania Right-to-Know: The following non-hazardous ingredients are present in the product at greater than 3%:

<u>Chemical Name</u>	<u>CAS No.</u>
Acrylic Resin	n/a
Sucrose Acetate Isobutyl Resin	n/a

California Proposition 65: WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer or birth defects and other reproductive harm:

<u>Chemical Name</u>	<u>CAS No.</u>
Toluol	00108-88-3

INTERNATIONAL REGULATIONS-AS FOLLOWS:

Canadian WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

Canadian WHMIS Class: No information available.

16. OTHER INFORMATION

HMIS Ratings: Health = 1; Flammability = 4; Reactivity = 3

Previous MSDS Revision Date: January 19, 1996

Volatile Organic Compounds (VOCS): 4.73 lbs/gal; 567 grams/ltr; 56% by weight

Legend: n/a = not applicable n/e = not established n/d = not determined