

MATERIAL SAFETY DATA SHEET

CR-14AM

Complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200.

GOODSON

Tools and Supplies for Engine Builders

156 Galewski Drive • P.O. Box 847 • Winona, MN 55987-0847
Toll-Free 1-800-533-8010 • Local 507-452-1830 • www.goodson.com

DATE OF PREPARATION: September 18, 2008

1. IDENTIFICATION:

Part No.: CR-14AM
Description: Magnaglo® Prepared Bath 14AM
NFPA Rating: Health 1, Flammability 1(aerosol 4), Reactivity 0
PIN (Canada): None
Emergency Phone: 800-688-4005 (24 hours)

2. HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>Wt. %</u>	<u>CAS #</u>	<u>TLV</u>	<u>PEL</u>	<u>LD50</u>	<u>LC50</u>
White Mineral Oil(petroleum)	60-100	8042-47-5	5mg/m	5mg/m	Not avail.	Not avail.
**Isobutane (propellant)	30	75-28-5	Not avail.	1000 ppm	Not avail.	Not avail.

**Aerosol only

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Bland oily liquid which may irritate the skin. Difficult to ignite, but will burn vigorously if engulfed in fire. Aerosol is extremely flammable.

POTENTIAL HEALTH EFFECTS

Skin Contact: May irritate by removing natural skin oils on long or repeated exposures.
Eyes: Possibly irritating.
Inhalation: Not significant. Isobutane vapors or heated bulk vapors may cause dizziness and nausea.
Ingestion: Not significant in small (mouthful) amounts.
Medical conditions that may be aggravated by exposure to product: None

4. FIRST AID

Skin Contact: Wash off with soap and water. Use soothing lotion.
Eyes: Rinse carefully under upper and lower eyelids using plenty of water.
Inhalation: Remove to fresh air if dizzy or nauseated.
Ingestion: Do not induce vomiting. Accidental ingestion of a single mouthful is not expected to cause significant harm.
NOTE: In all severe cases, contact physician immediately. Local telephone operators can furnish number of regional poison control center.

5. FIRE HAZARD

Conditions of Flammability: Bulk: Can ignite if heated above 200°F. Aerosol: Spraying near flames or arcs will ignite the spray mist.

Flash Point (bulk): Minimum 200°F (93°C) (Pensky-Martens closed cup).

Flammable limits in air: 1% to 6%

Extinguishing Media: Carbon dioxide, foam.

Special Firefighting Procedures: Keep containers cool with water spray. Do not spray water on burning 14-AM. It will float and spread the fire.

Hazardous Combustion Products: Smoke, soot, oxides of carbon.

Unusual Fire Hazards: Aerosol cans may burst if heated above 130°F (54°C) and spray contents into a fire.